

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
31 March 2005 (31.03.2005)

PCT

(10) International Publication Number  
**WO 2005/028868 A1**

(51) International Patent Classification<sup>7</sup>: **F04B 39/00**,  
39/12

(74) Agent: **PARK, Jang-Won**; Jewoo Bldg. 5th Floor, 200  
Nonhyun-Dong, Gangnam-Gu, Seoul, 135-010 (KR).

(21) International Application Number:  
PCT/KR2004/002223

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG,  
MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH,  
PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN,  
TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(22) International Filing Date:  
2 September 2004 (02.09.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
10-2003-0065648  
22 September 2003 (22.09.2003) KR

(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,  
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,  
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,  
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,  
GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (for all designated States except US): **LG  
ELECTRONICS INC.** [KR/KR]; 20 Yoido-Dong, Yong-  
dungpo-Gu, Seoul 150-010 (KR).

(72) Inventor; and


(75) Inventor/Applicant (for US only): **LEE, Min-Woo**  
[KR/KR]; Booyoung Scha Apt., 904-1907 Seokbong  
maeul, Mugye-Ri, Jangyu-myeon, Gimhae, Gyeongsang-  
nam-Do, 621-833 (KR).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.

(54) Title: **RECIPROCATING COMPRESSOR HAVING SUPPORTING UNIT ATTENUATING LATERAL DISPLACEMENT THEREOF**



(57) Abstract: A reciprocating compressor comprises a casing including a suction pipe (SP) through which a fluid is introduced from the outside and a discharge pipe (DP) through which the fluid is discharged outside and forming a predetermined internal space; a compressor main body (700) positioned in the casing (100), compressing the fluid introduced through the suction pipe (SP) with a linear reciprocating motion of a piston (420) and discharging the compressed fluid through the discharge pipe (DP); and a supporting unit (600) including a plurality of coil springs connecting the compressor main body (700) to the casing (100), wherein the plurality of coil springs (610, 620) includes, respectively, end coils (590) tightly wound so as to be fixed to one surface of the compressor main body (700) and to one surface of the casing (100) and an inner coil (580) having at least one part which is tightly wound and positioned between the end coils (590), thereby minimizing the lateral vibration of the compressor, which is generated in a direction that a reciprocating motor is operated in operation of the reciprocating compressor.

WO 2005/028868 A1